Publish: February 9th, 2024 & February 23rd, 2024

# **NOTICE TO BIDDERS**

Notice is hereby given that the Lake County Commission will receive sealed bids for the following materials or services at the office of the Lake County Auditor, 200 East Center St. Madison, SD 57042, until 10:00 am on the 1<sup>st</sup> day of March 2024. All bids must be mailed or delivered to the above address. At 10:30 am, all bids will be publicly opened and read in the commission room.

Sealed bids for the following materials or services are requested:

- 1. Liquid Asphalt
- 2. Asphalt Patching Material
- 3. Red Crushed Quartzite Chips
- 4. 3/8 Pea Rock
- 5. Rip-Rap (Class B red rock) or (Class C Field Stone)
- 6. Polypropylene Culverts
- 7. Road Sealant & Rubberized Mastic Sealant
- 8. Ice Sand
- 9. Aggregate Base Stabilizer
- 10. Vehicle Engine Oils
- 11. Milling/Reclaiming
- 12. Equipment Rental

Plainly mark on the outside envelope "Liquid Asphalt", "Asphalt Patching Material", "Red Crushed Quartzite Chips", "3/8 Pea Rock", "Rip-Rap (Class B red rock) or (Class C Field Stone)",

"Polypropylene Culverts", "Road Sealant & Rubberized Mastic Sealant", "Ice Sand", "Aggregate Base Stabilizer", "Vehicle Engine Oils", "Milling/Reclaiming", "Equipment Rental".

Specifications for the above items may be obtained at the office of the Lake County Highway Department and on the Lake County website at www.lake.sd.gov.

The Commissioners reserve the right to reject any or all bids.

By order of the Board of Lake County Commissioners.

/s/ Paula Barrick

**Lake County Auditor** 

PUBLIC NOTICE PUBLISHED TWICE	
@ THE TOTAL APPROXIMATE COST OF \$	

# **LIQUID ASPHALT BID SPECIFICATIONS**

# **Liquid Asphalt:**

Item 1: Cut-back oils: MC70, MC250-(1) Load and MC3000

Item 2: Emulsions Oils: CRS 2P

Item 3: CSS-1h Item 4: Water

- 1. Price per ton in transport load to be delivered F.O.B as needed to location designated in Lake County. County will sealcoat approximately 20 miles.
- 2. Lake County will have 2 hours to unload trucks before demurrage charges start. Demurrage rate cost per hour must be included on the bid.
- 3. Oil must be delivered at application temperature or oil will be rejected at bidder's expense.
- 4. All oils must meet the current SD Standard Specifications.
- 5. Bidder must submit a certificate of insurance for a minimum of one million dollars liability insurance.
- 6. Bid shall be firm and will be effective from 3/1/2024 to 2/28/2025.
- 7. All bid prices to include any applicable taxes and/or fees.
- 8. Bidder must sign a Lake County Purchase Agreement.
- 9. The Notice to Bidders shall be considered a part of these specifications.
- 10. The Lake County Board of Commissioners reserves the right to accept or reject any or all bids.

Item 1: Cut back oils: MC70, MC250-(1) Load and MC3000  Price per ton:				
Item 2: Emulsions Oils: CRS 2P				
Price per ton:				
Item 3: CSS-1h				
Price per ton:				
Item 4: Water				
Price per ton:				
<b>BIDDER'S INFORMATION:</b>				
Name/Title:				
Company:	_			
Address:	_			
City, State, Zip:	_			
Phone/Email:	_			
LIQUID ASPHALT BID SPECIFICATIONS AND PROPOSAL				

# **ASPHALT PATCHING MATERIAL SPECIFICATIONS**

- 1. Bidder must furnish all materials, equipment and labor necessary weigh and place in a County Vehicle or load on to County Equipment as needed.
- 2. Bidder must provide locations for F.O.B. plants.
- 3. Bidder must furnish scale.
- 4. Bidder must submit a certificate of insurance for a minimum of one million dollars liability insurance.
- 5. Bid shall be firm and will be effective from 3/1/2024 to 2/28/2025.
- 6. All bid prices to include any applicable taxes and/or fees.
- 7. Bidder must sign a Lake County Purchase Agreement.
- 8. The Notice to Bidders shall be considered a part of these specifications.
- 9. The Lake County Board of Commissioners reserves the right to accept or reject any or all bids.

F.O.B. Plant Location:				
Price per ton: \$				
BIDDER'S INFORMATION:				
Authorized Agent:	_			
Company:	_			
Address:	-			
City, State, Zip:	_			
Phone/Email:				

# 3/8" AND 1/2" QUARTZITE CHIPS BID SPECIFICATIONS

- 1. Bidder must furnish all materials, equipment and labor necessary to crush, weigh and place in a County Vehicle or load on to County Equipment as needed.
- 2. Bidder must provide locations for F.O.B. plants.
- 3. Bidder must furnish scale.
- 4. The quartzite chips must conform to the specifications for 3/8" and ½" Quartzite Chips as stated in 2015 Edition of South Dakota Standard Specifications for Roads & Bridges. Section 882-Type 2A & 2B.

# 881.2 SPECIFIC REQUIREMENTS

REQUIREMENTS TY		PE 1		TYPE 2		Γ
	Α	В	Α	В	С	
Sieve			Percent I	assing		
5/8 inch						
1/2 inch					100	Γ
3/8 inch	100	100	100	100	0-100	Γ
1/4 inch	25-70				0-70	Γ
#4	0-25	0-75	0-70	0-60	0-15	Γ
#8	0-5	0-30	0-28	0-18	0-5	Γ
#40		0-6	0-4	0-4		
#200	0-1.3	0-3.0	0-3.0	0-1.3	0-1.0	
		Other Pro	perties		•	_
Flakiness Index (max)	30%		30%	30%	30%	
Plasticity Index (max)	3	3	3	3	NP	
LA Abrasion Loss (max)	40%	40%	40%	40%	40%	Г
Soundness Loss (max)	12%	12%	12%	12%	12%	Γ
Crushed Particles (min) +#4 Sieve			50% 2-CF	100% 2-CF	50% 2-CF	
Foot Notes		<sub>*</sub> 1	*1	*1		

<sup>\*1</sup> The plasticity index may be waived if not more than 4% of the material passes the #40 sieve

- 5. Lake County may require testing material as per specifications, 881.3 sampling and testing, prior to application, which will be at the cost of the Bidder.
- 6. Method of Measurement and Basis for Payment:
  - a. The quartzite chips must be measured in tons (2,000 lbs) and tenths thereof to the nearest tenth of a ton
  - b. Payment for the quartzite chips will be paid for at the contract unit price per ton stipulated in the proposal which price and payment shall be full compensation for furnishing all labor, equipment, tool and materials required to satisfactorily strip the pits, handle the 3/8" pea rock and waste, crush, load, weigh, and place the 3/8" pea rock in a County vehicle or loaded on County equipment.
- 7. Bidder must submit a certificate of insurance for a minimum of one million dollars liability insurance.

- 8. Bid shall be firm and will be effective from 3/1/2024 to 2/28/2025.
- 9. All bid prices to include any applicable taxes and/or fees.
- 10. Bidder must sign a Lake County Purchase Agreement.
- 11. The Notice to Bidders shall be considered a part of these specifications.
- 12. The Lake County Board of Commissioners reserves the right to accept or reject any or all bids.

F.O.B. Plant Location:	
3/8" Price per ton: \$	
F.O.B. Plant Location:	
1/2" Price per ton: \$	
<b>BIDDER'S INFORMATION:</b>	
Name/Title:	
Company:	-
Address:	
City, State, Zip:	-
Phone/Email:	

# 3/8" PEA ROCK SPECIFICATIONS

- 1. Bidder must furnish all materials, equipment and labor necessary to crush, weigh and place in a County Vehicle or load on to County Equipment as needed.
- 2. Bidder must provide locations for F.O.B. plants.
- 3. Bidder must furnish scale.
- 4. The 3/8" pea rock must conform to Section 881.2, Type 1, Class B Aggregate, 2015 Standard Specifications for Asphalt Surface Treatment Aggregate.

#### 881.2 SPECIFIC REQUIREMENTS

REQUIREMENTS	TY	PE 1		TYPE 2		Γ
	Α	В	Α	В	С	1
Sieve			Percent I	Passing		_
5/8 inch						
1/2 inch					100	Γ
3/8 inch	100	100	100	100	0-100	Ī
1/4 inch	25-70				0-70	Г
#4	0-25	0-75	0-70	0-60	0-15	Γ
#8	0-5	0-30	0-28	0-18	0-5	Ī
#40		0-6	0-4	0-4		Г
#200	0-1.3	0-3.0	0-3.0	0-1.3	0-1.0	
		Other Pro	operties		•	
Flakiness Index (max)	30%		30%	30%	30%	
Plasticity Index (max)	3	3	3	3	NP	
LA Abrasion Loss (max)	40%	40%	40%	40%	40%	Γ
Soundness Loss (max)	12%	12%	12%	12%	12%	
Crushed Particles (min) +#4 Sieve			50% 2-CF	100% 2-CF	50% 2-CF	
Foot Notes		*1	<b>*</b> 1	*1		

<sup>\*1</sup> The plasticity index may be waived if not more than 4% of the material passes the #40 sieve

- 5. Lake County may require testing material as per specifications, 881.3 sampling and testing, prior to application, which will be at the cost of the Bidder.
- 6. Method of Measurement and Basis for Payment:
  - a. The 3/8" pea rock must be measured in tons (2,000 lbs) and tenths thereof to the nearest tenth of a ton
  - b. Payment for 3/8" pea rock will be paid for at the contract unit price per ton stipulated in the proposal which price and payment shall be full compensation for furnishing all labor, equipment, tool and materials required to satisfactorily strip the pits, handle the 3/8" pea rock and waste, crush, load, weigh, and place the 3/8" pea rock in a County vehicle or loaded on County equipment.
- 7. Bidder must submit a certificate of insurance for a minimum of one million dollars liability insurance.
- 8. Bid shall be firm and will be effective from 3/1/2024 to 2/28/2025.
- 9. All bid prices to include any applicable taxes and/or fees.
- 10. Bidder must sign a Lake County Purchase Agreement.
- 11. The Notice to Bidders shall be considered a part of these specifications.
- 12. The Lake County Board of Commissioners reserves the right to accept or reject any or all bids.

F.O.B. Plant Location:				
Price per ton: \$				
BIDDER'S INFORMATION:				
Name/Title:				
Company:	_			
Address:	_			
City, State, Zip:	_			
Phone/Email:	_			

# RIP-RAP (CLASS B RED ROCK) OR (CLASS C FIELD STONE) BID SPECIFICATIONS

- 1. Bidder must furnish all materials, equipment and labor necessary to crush, weigh and place in a County Vehicle or load on to County Equipment as needed.
- 2. Bidder must provide locations for F.O.B. plants.
- 3. Bidder must furnish scale.
- 4. The Class B Red Rock or Class C Field Stone must conform to the Section 830.1 for Rip Rap Requirements.

RIP RAP 830

#### 830.1 REQUIREMENTS

A. Riprap: Stone for riprap shall be hard and durable and shall have a minimum weight of 155 pounds per cubic foot. Riprap may be ledge rock or field stone. If field stone is utilized for Class C or larger, the stone shall have a minimum of 2 crushed faces as defined under SD 211. Stone shall be free from overburden, spoil, shale, and organic material. The riprap stone shall meet the following gradation requirements:

Riprap Class	Rock Size*1 in feet	Rock Size in pounds	Percent of Riprap Smaller Than
	1.30	200	100
Α	0.95	75	50
	0.40	5	15
	1.80	500	100
В	1.30	200	50
	0.40	5	15
	2.25	1000	100
С	1.80	500	50
	0.95	75	15
D	2.85	2000	100
	2.25	1000	50
	1.80	500	15
	3.60	4000	100
E	2.85	2000	50
	2.25	1000	15
	4.50	8000	100
F	3.60	4000	50
	2.85	2000	15

<sup>\*1</sup> Based on a specific gravity of 2.65 and spherical shape.

The riprap class is the median particle weight with 50% of the material smaller and 50% of the material larger.

Each load of riprap shall be well graded from the smallest to the maximum size specified.

#### B. Testing:

Specific Gravity......SD 210

5. Lake County may require testing material as per specifications, sampling and testing, prior to application, which will be at the cost of the Bidder.

- 6. Method of Measurement and Basis for Payment:
  - a. The rip rap must be measured in tons (2,000 lbs) and tenths thereof to the nearest tenth of a ton
  - b. Payment for rip rap will be paid for at the contract unit price per ton stipulated in the proposal which price and payment shall be full compensation for furnishing all labor, equipment, tool and materials required to satisfactorily strip the pits, handle the rip rap, crush, load, weigh, and place the rip rap in a County vehicle or loaded on County equipment.
- 7. Bidder must submit a certificate of insurance for a minimum of one million dollars liability insurance.
- 8. Bid shall be firm and will be effective from 3/1/2024 to 2/28/2025.
- 9. All bid prices to include any applicable taxes and/or fees.
- 10. Bidder must sign a Lake County Purchase Agreement.
- 11. The Notice to Bidders shall be considered a part of these specifications.
- 12. The Lake County Board of Commissioners reserves the right to accept or reject any or all bids.

**PROPOSAL** 

# F.O.B. Plant Location: Price per ton CLASS B RED ROCK: \$ F.O.B. Plant Location: Price per ton CLASS C FIELD STONE: \$ BIDDER'S INFORMATION: Name/Title: Company: Address: City, State, Zip:

# POLYPROPYLENE CULVERT BID SPECIFICATIONS

# **Polypropylene Culverts**

Item 1: 12" to 60" round polypropylene pipe shall meet the requirements of AASHTO M330 Type S (dual wall) or Type D (triple wall)

Item 2: Mar Mac Polyseal coupler 18" and 24"

- 1. Shipping must be included in the bid price per foot.
- 2. Culverts must meet AASHTO Designation (American Association of State Highway & Transportation Officials) M330 is Standard Specification for Polypropylene Pipe, 12" to 60" diameter.
- 3. Bid shall be firm and will be effective from 3/1/2024 to 2/28/2025.
- 4. All bid prices to include any applicable taxes and/or fees.
- 5. Bidder must submit a certificate of insurance for a minimum of one million dollars liability insurance.
- 6. Bidder must sign a Lake County Purchase Agreement.
- 7. The Notice to Bidders shall be considered a part of these specifications.
- 8. The Lake County Board of Commissioners reserves the right to accept or reject any or all bids.

# **PROPOSAL**

Item 1: 12" to 60" round polypropylene pipe shall meet Type S (dual wall) or Type D (triple wall)	the requirements of AASHTO M330
Price per foot:	
Item 2: Mar Mac Polyseal coupler 18" and 24"	
Price:	
BIDDER'S INFORMATION:	
Name/Title:	
Company:	
Address:	
City, State, Zip:	-

# ROAD SEALANT AND RUBBERIZED MASTIC SEALANT BID SPECIFICATIONS

## Item 1: Mastic One Specifications



PRODUCT DATA SHEET

**MASTIC ONE** 

**PART NO. 33339** 

6165 W. Detroit St. • Chandler, AZ 85226 1-800-528-8242 • 1-602-276-0406 • FAX 1-480-961-0513 www.crafco.com

#### READ BEFORE USING THIS PRODUCT

GENERAL Mastic One is a hot applied, pourable, aggregate filled, black color, polymer modified asphalt pavement repair mastic. Mastic One is used for sealing, filling and repairing many distresses in both asphalt concrete and portland cement concrete pavements and bridge deck surfaces that are larger than those typically repaired by crack or joint sealing, but smaller than repairs requiring remove and replace patching procedures. Typical uses include sealing, filling and leveling of wide transverse or longitudinal cracks and joints, filling potholes and utility cuts, localized skin patch repairs, repairs prior to surface treatments, and leveling bridge approaches or faulted areas. When properly applied, Mastic One forms a well bonded, flexible, durable, traffic resistant repair. To use, Mastic One is placed into an appropriate melter (Crafco Patcher I or II), mixed and heated until application temperature is reached, poured into the prepared repair area and then leveled. Mastic One is formulated to provide neat feathered edge installation. Mastic One is then ready for traffic when it has cooled and solidified. VOC = 0 g/l.

PROPERTIES Properties of the binder, aggregate and appropriately blended and heated Mastic One are as follows:

#### Property

#### Requirement

#### POLYMER MODIFIED BINDER

Cone Penetration, 77°F (25°C) (ASTM D5329) Cone Penetration, 122°F (50°C) (ASTM D5329) Softening Point (ASTM D36) Flexibility (1\*[25.4 mm], 180°, 10 sec) (ASTM D3111 modified)

60 max 120 max 200°F (93°C) min Pass at 32°F (0°C)

#### **AGGREGATE**

Abrasion Resistance (ASTM C131)

35% max

#### BLENDED PRODUCT

Flexibility, 32°F (0°C) (PTM 3) Adhesion, 77°F (25°C) (PTM 4) Specific Gravity Minimum Application Temperature Maximum Application Temperature

Pass 25 PSI (172 KPA) min 1.7 – 2.0 375°F (190°C) 400°F (204°C)

Note: Due to unique properties of Mastic One, modified test procedures are required. Test methods PTM 3, 4 are available from Crafco.

INSTALLATION The density of Mastic One is 116 pcf (+/- 3%) and the weight per gallon is 15.5 lbs/gal (1.86 kg/li) at 60°F (15.5°C). Prior to use, the user must read and follow Installation Instructions for Mastic One to verify proper product selection, heating methods, pavement preparation procedures, application geometry, usage precautions and safety procedures. These instructions are available at www.crafco.com and provided with each pallet of Mastic One

PACKAGING Mastic One can be supplied in either standard cardboard boxes, or in meltable, boxless PLEXI-melt packaging. Each package contains premeasured poly- mer modified binder and aggregate. Both packaging types are labeled in accordance with OSHA and GHS requirements; include Installation Instructions; are sold by net weight; are supplied interlock stacked on 48 by 40 inch 4-way pallets; can be stored outside; and are covered with a weather resistant pallet cover and 2 layers of UV protected stretch wrap.

Box packaging consists of cardboard boxes containing 40 lb of product with 60 boxes per pallet. Boxes contain a quick melting release film enabling easy removal of product from the box. Boxes are tape closed, without any staples.

PLEXI-melt packaging consists of 30 lb. (13.6 kg) blocks of product with 70 packages per pallet, weighing 2100 lb. (952 kg). To use, the pallet wrap is removed, and individual blocks are placed in the melter. There are no cardboard boxes or other cardboard components to open, empty, handle, or dispose of. PLEXI-melt packaging quickly melts into the product without affecting specification conformance.

WARRANTY CRAFCO, Inc. warrants that CRAFCO products meet applicable ASTM, AASHTO, Federal or State specifications at time of shipment. Techniques used for the preparation of the cracks and joints prior to sealing or filling are beyond our control as are the use and application of the products; therefore, Crafco shall not be responsible for improperly applied or misused products. Remedies against Crafco, Inc., as agreed to by Crafco, are limited to replacing nonconforming product or refund (full or partial) of purchase price from Crafco, Inc. All claims for breach of this warranty must be made within three (3) months of the date of use or twelve

(12) months from the date of delivery by Crafco, Inc. whichever is earlier. There shall be no other warranties expressed or implied. For optimum performance, follow Crafco recommendations for product installation.

©2018 Crafco, Inc. March





PRODUCT DATA SHEET **ROADSAVER 221** 

PART NO. 34221

SEPTEMBER 2016

6165 W Detroit St. . Chandler AZ 85226 +1 (602) 276-0406 • +1 (800) 528-8242 • FAX +1 (480) 961-0513 www.crafco.com

READ BEFORE USING THIS PRODUCT

GENERAL Crafco RoadSaver 221 sealant is a hot-applied asphalt based product used to seal and fill cracks and joints in asphalt or Portland cement concrete pavements in hot to cold climates. RoadSaver 221 is supplied in solid form which when melted and properly applied forms a resilient, adhesive and flexible compound that resists cracking in the winter and is resistant to flow and pick-up at summer temperatures. RoadSaver 221 is used in highway, street, and airfield pavements and is applied to pavement cracks and joints using either pressure feed melter applicators or pour pots. At application temperature RoadSaver 221 is a free flowing, self-leveling product. RoadSaver 221 is a widely used, excellent performing sealant that has been a quality Crafco product for over 30 years. VOC = 0 g/l.

USAGE GUIDELINES RoadSaver 221 is applicable for Sealant / Reservoir Use or Filler / Overband Use in hot to cold climates with low and high pavement temperatures identified in the charts. Pavement temperatures for the project location are determined at 98% reliability using FHWA LTPPBind V 3.1, and sealant or filler use is determined following Crafco Product Selection Procedures

Applicable Pavement Temperatures

High Temperature (°C) -34

Sealant / Reservoir Use

High Temperature (°C) °C 52 58 64 70 76 82 -28

Filler / Overband Use

SPECIFICATION CONFORMANCE RoadSaver 221 meets all requirement of ASTM D6690 (AASHTO M324), Type II, "Joint and Crack Sealants, Hot-Applied, for Concrete and Asphalt Pavements", (formerly ASTM D3405 and AASHTO M301). It also exceeds requirements of ASTM D6690 (AASHTO M324), Type I, (formerly ASTM D1190, AASHTO M173), and Federal Specification SS-S-164.

> Test Cone Penetration Softening Point Resilience Bond, -20°F (-29°C), 50% ext. Asphalt Compatibility Minimum Application Temperature Maximum Heating Temperature

ASTM D6690 (AASHTO M324) Type II Spec. Limits 90 max. 176°F (80°C) min. 60% min. Pass 3 cycles Compatible 380°F (193°C

INSTALLATION The unit weight of Crafco RoadSaver 221 is 10.5 lbs. per gallon (1.26 kg/L) at 60 °F (15.5 °C). Prior to use, the user must read and follow installation instructions for Hot-Applied RoadSaver, PolyFlex, Parking Lot and Asphalt Rubber Products to verify proper product selection, heating methods, pavement preparation procedures, application geometry, usage precautions and safety procedures. These instructions are provided with each pallet of product.

PACKAGING Product is supplied in either cardboard boxes, or in meltable, boxless PLEXI-melt packaging. Both package types are labeled in accordance with OSHA, GHS, and specification requirements; are sold by net weight; are interlock stacked on 48 x 40 in. (122 x102

- empty harding composition of SPLEXI-melt packaging consists of 30 lb. (13.6 kg) blocks or placed in the melter. There are no cardboard boxes or other cardboard components to open, empty, handle, or dispose of. PLEXI-melt packaging quickly melts into the product without affecting specification conformance.

WARRANTY CRAFCO, Inc. warrants that CRAFCO products meet applicable ASTM, AASHTO, Federal or State specifications at time of shipment. Techniques used for the preparation of the cracks and joints prior to sealing or filling are beyond our control as are the use and of similarity terminques used for the preparation of the cracks and joints prior to sealing or filling are beyond our control as are the use and application of the products; therefore, Crafco shall not be responsible for improperly applied or misused products. Remedies against Crafco, Inc., as agreed to by Crafco, are limited to replacing nonconforming product or refund (full or partial) of purchase price from Crafco, Inc. All claims for breach of this warranty must be made within three (3) months of the date of use or twelve (12) months from the date of delivery by Crafco, Inc. whichever is earlier. There shall be no other warranties expressed or implied. For optimum performance, follow Crafco recommendations for product installation.

@2016, Crafco, Inc. #A1110

# 4. Package Specifications:



SPECIFICATIONS
PLEXI-MELT<sup>TM</sup> PACKAGE

**JANUARY 2016** 

6165 W Detroit St. • Chandler AZ 85226 +1 (602) 276-0406 • +1 (800) 528-8242 • FAX +1 (480) 961-0513 www.crafco.com

Product shall be supplied in 30 lb. (13.6 kg) completely meltable packages that are interlock stacked on pallets containing 2100 lb. (952 kg) of product. The individual packages and palletized unit shall not contain any cardboard components to open, empty, handle, or dispose of. Packages shall be labeled in accordance with OSHA, GHS and ASTM requirements. The packages and palletized unit shall be water and weather resistant and shall be able to be stored outside.

The individual packages of product shall be encased in a high-strength, low-density, protective covering that quickly melts into the product at normal use temperatures without affecting product installation characteristics or specification conformance.

The protective covering shall not weigh more than 0.50% of the product weight and shall have the following properties:

Thickness (ASTM D1777, 7.15 psi, 0.625 in. dia. presser) 0.004-0.008 in. (0.10-0.20 mm)

Puncture Resistance (ASTM E 154) 75 lb. (334N) minimum

Tensile Strength (ASTM D5035, cut strip, 2 in. /min) 20 lb. /in. (35N/cm) minimum

Density (ASTM D792) 0.50 g/cc maximum

- 5. Price shall be F.O.B. Lake County Highway Shop. All materials must meet South Dakota Department of Highway Specifications.
- 6. Bid shall be firm and will be effective from 3/1/2024 to 2/28/2025.
- 7. All bid prices to include any applicable taxes and/or fees.
- 8. Bidder must submit a certificate of insurance for a minimum of one million dollars liability insurance.
- 9. Bidder must sign a Lake County Purchase Agreement.
- 10. The Notice to Bidders shall be considered a part of these specifications.
- 11. The Lake County Board of Commissioners reserves the right to accept or reject any or all bids.

<b>Mastic One:</b> \$	/per pound
Roadsaver 221 · \$	/ner noun

# **BIDDER'S INFORMATION:**

Name/Title:
Company:
Address:
City, State, Zip:
Phone/Email:

# **ICE SAND SPECIFICATIONS**

			TOD STITLE STEETING
1.	inclusi		ng gradation is recommended when purchasing abrasive material or for ve material contract specifications:
	a.	a: a:	0/P
		Sieve Size	
		3/8"	
	d.	#4	80-100
	e.	#10 #40	40-80
	f.	#40	5-35
		#200	
			it not to exceed 26, plastic index not to exceed 3
2.			sh all materials, equipment and labor necessary weigh and place in a
	County	y Vehicle or	load on to County Equipment as needed.
3.	Bidder	must provi	de locations for F.O.B. plants.
4.	Bidder	must furnis	sh scale.
5.	Bidder	must subm	it a certificate of insurance for a minimum of one million dollars liability
	insurar	nce.	
6.	Bid sha	all be firm a	and will be effective from 3/1/2024 to 2/28/2025.
7.	All bid	l prices to in	nclude any applicable taxes and/or fees.
8.	Bidder	must sign a	a Lake County Purchase Agreement.
9.	The No	otice to Bid	ders shall be considered a part of these specifications.
			Board of Commissioners reserves the right to accept or reject any or all
	bids.	,	
			PROPOSAL
F.C	).B. Pla	nt Locatio	n:
Bio	l Ice Sa	ınd picked	up at Vendor's Pit: \$
Bio	l Ice Sa	ınd Deliver	ed to County shop yard: \$
BI	DDER'	S INFORM	<u>IATION:</u>
Na	me/Title	e:	
Co	mpany:		
	dress:		

City, State, Zip:

# **AGGREGATE BASE STABILIZER SPECIFICATIONS**

- 1. Only bids for aggregate base stabilizer (Base One) or equivalent will be accepted.
- 2. Amount to be purchased and applied will be determined by bid price, budget, and weather conditions no maximum or minimum amount will be guaranteed.
- 3. Bidder must submit a certificate of insurance for a minimum of one million dollars liability insurance.
- 4. Bid shall be firm and will be effective from 3/1/2024 to 2/28/2025.
- 5. All bid prices to include any applicable taxes and/or fees.
- 6. Bidder must sign a Lake County Purchase Agreement.
- 7. The Notice to Bidders shall be considered a part of these specifications.
- 8. The Lake County Board of Commissioners reserves the right to accept or reject any or all bids.

**PROPOSAL** 

# F.O.B. Plant Location: \_\_\_\_\_\_\_Price per gallon: \$\_\_\_\_\_\_

# 

# **VEHICLE ENGINE OILS (PETROLEUM PRODUCTS) BID SPECIFICATIONS**

- 1. A laboratory test should accompany all oil bids to meet proper specifications for diesel engines.
- 2. All products must be delivered as needed to the Lake County Highway Department.
- 3. All products must be delivered in 30-gallon barrels.
- 4. Bid shall be firm and will be effective from 3/1/2024 to 2/28/2025.
- 5. All bid prices to include any applicable taxes and/or fees.
- 6. Bidder must submit a certificate of insurance for a minimum of one million dollars liability insurance.
- 7. Bidder must sign a Lake County Purchase Agreement.
- 8. The Notice to Bidders shall be considered a part of these specifications.
- 9. The Lake County Board of Commissioners reserves the right to accept or reject any or all bids.

Product	Price Per Gallon
Automatic Oil (Dexron III)	\$
Synthetic Automatic Transmission Fluid-Allison	
Approved	\$
Series 300 Oil:	\$
SAE 80W90 Extreme Pressure Sulfo-Chloro-Lead	\$
Heat Transfer Oil	
Flash point 450°F Minimum	
Pour point 10°F Maximum	
Viscosity, SUS (Saybolt universal seconds	
100°F 300-320 seconds	
130°F 150-160 seconds	
Viscosity index 90 minumum	\$
Series 200 oil	
SAE 30	\$
10W30	\$
5W20	\$
5W30	\$
Caterpillar TO-4 Specification	
10W	\$
30W	\$
High Temp Grease Gun by the Tube	\$

# BIDDER'S INFORMATION: Name/Title:

Company:

Address:

City, State, Zip:

# FULL OPERATION MILLING / RECLAIMING EQUIPMENT WITH OPERATOR FOR CONSTRUCTION AND MAINTENANCE REPAIRS BID SPECIFICATIONS

- 1. Successful bidder will be working along with the Lake County Highway Department to complete the projects.
- 2. Bidder must submit a certificate of insurance for a minimum of one million dollars liability insurance.
- 3. <u>Proposal-Guaranty:</u> No deposit or bond will be required at time of bid opening.
- 4. <u>Performance Bond:</u> Lake County will give notice to the successful bidder that their proposal has been accepted and said bidder shall within ten (10) days thereafter enter into a Contract with Lake County and said bidders shall then be required to furnish the following: Certificates of Insurance as per bid specifications or requested from Lake County. Lake County must be listed as additional insured on all Certificates of Insurance.
- 5. Bids shall include all applicable taxes and fees for materials furnished and/or installed by the Contractor and all applicable taxes and fees for materials supplied by the County. Lake County is exempt from all State Sales Tax.
- 6. Bid shall be firm and will be effective from 3/1/2024 to 2/28/2025.
- 7. All bid prices to include any applicable taxes and/or fees.
- 8. Bidder must sign a Lake County Purchase Agreement.
- 9. The Notice to Bidders shall be considered a part of these specifications.
- 10. The Lake County Board of Commissioners reserves the right to accept or reject any or all bids.

Grind Only:
Grind only (syd) \$
Project Mobilization \$
Grind with Lay-back Process:
Grind (syd) \$
Project Mobilization \$
Grind with additive injection & lay back process County will furnish gravel with additive
Grind (syd) \$
Project Mobilization: \$

Milling
Grind (syd) \$
Project Mobilization \$
<b>BIDDER'S INFORMATION:</b>
Name/Title:
Company:
Address:
City, State, Zip:
Phone/Email:

# EQUIPMENT RENTAL BID SPECIFICATIONS FULL OPERATION RENTAL SERVICES OF GRAVEL TRUCKS & ROAD MACHINERY

- 1. Bid must include all associated costs for full operation. For "Bridge Equipment", "Crushing Equipment", "Patching Equipment" and "Paving Equipment", the rate must include all equipment and personnel costs for the entire operation. "Paving Equipment" and "Patching Equipment" hourly rate should NOT include trucking costs. (Trucks must be bid separately.)
- 2. Successful bidders will be working along with the Lake County Highway Department to complete the projects.
- 3. <u>Proposal Guaranty:</u> No deposit or bond will be required at the time of bid opening.
- 4. Performance Bond: Lake County will give notice to the successful bidder that their proposal has been accepted and said bidder shall, within ten (10) days thereafter, enter into a Contract for Rental Equipment with Lake County. Bidders shall then be required to furnish the following: Prior to working with Lake County, certificates of insurance as per bid specifications or requested from Lake County, and Lake County must be listed as additional insured on all Certificates of Insurance.
- 5. Bid shall be firm and will be effective from 3/1/2024 to 2/28/2025.
- 6. All bid prices to include any applicable taxes and fees for materials furnished and/or installed by the Contractor and all applicable taxes and fees for materials supplied by the County. South Dakota Contractor's Excise and Use Taxes are to be included in the Unit Bid Price for hourly, monthly, and yearly rates.
- 7. The Notice to Bidders shall be considered a part of these specifications.
- 8. The Lake County Board of Commissioners reserves the right to accept or reject any or all bids.

# FULL OPERATION RENTAL EQUIPMENT PROPOSAL

<b>BULLDOZERS:</b>		
Make/Model	Size/Capacity	Rate/Hour

EXCAVATORS:		
Make/Model	Size/Capacity	Rate/Hour

LOADERS:	
Size/Capacity	Rate/Hour
	Size/Capacity

SCRAPERS:		
Make/Model	Size/Capacity	Rate/Hour

COMPACTION EQUIPMENT:		
Make/Model	Size/Capacity	Rate/Hour

TRACTOR-TRAILER/PUP 40 TON MINIMUM		
Make/Model	Size/Capacity	Rate/Hour

ASPHALT TRUCKS:		
Make/Model	Size/Capacity	Rate/Hour

	PERATION CREWS	C 11
include all costs for equ	uipment and personnel to	Tully perform each activ
	EQUIPMENT (trucks bid	
Make/Model	Size/Capacity	Rate/Hour
D.A.	TOHING FOLLOWEN	г
Make/Model	Size/Capacity	Rate/Hour
TVTUKE/TVTOGET	Size/ Capacity	Rate/110th
DADE ODEDATION	EQUIDMENT	
BARE OPERATION	<u>EQUIPMENT</u>	
Describes Constant	/m = n 4le	
Recycling Crusher: \$	/month	
Live Bottom Asphalt T	railer \$/month	
BIDDER'S INFORM	ATION:	
Name/Title:		<u> </u>
Company:		
Address:		
City, State, Zip:		
Phone/Email:		